MATERIAL SAFETY DATA SHEET

Lancer Sales USA, Inc.

1150 Emma Oaks Tr, Ste 140, Lake Mary, FL 32746

DATE ISSUED: 12-MAR-13

SECTION I		PRODUCT IDENTIFICATION		
PRODUCT NAME	:	LANCERCLEAN	, Sodium Hydroxide	
CHEMICAL NAME	:	HIGHLY ALKALINE DETERGENT BLEND		
Formula	:	PROPRIETARY		
DOT HAZARD CLASS	:	CORROSIVE LIQUID, SODIUM HYDROXIDE SOLUTION,		
		8, UN #1824, PG II		
HAZARD RATING (NFPA 704)		HAZARD RATING	PROTECTIVE EQUIPMENT	
Health: 3		0=MINIMAL	A=GOGGLES	
Fire: 0		1=SLIGHT	B=GOGGLES, GLOVES	
REACTIVITY: 2		2=MODERATE	C=GOGGLES, GLOVES, APRON	
PROTECTIVE EQUIPMENT: D		3=Serious	D= Goggles, Gloves, Apron, Face Shield	
		4=Severe	E= Goggles, Gloves, Respirator	

CHEMTREC'S 24 HOUR EMERGENCY TELEPHONE NUMBER 800-424-9300

SECTION II

HAZARDOUS INGREDIENTS

Substances listed in this section are those identified as being present at a concentration of 1% or greater, or 0.1% if the substance is on the list of potential carcinogens cited in OSHA hazard communication standard.

MATERIAL	CAS#	TLV	PEL
Sodium hydroxide	1310-73-2	2mg/m³	2мg/м ³
Sodium silicate	1344-09-8	NONE	NONE

SECTION III

PHYSICAL DATA

BOILING POINT: 212 °F VAPOR PRESSURE: (AIR=1): >1 VAPOR DENSITY: (AIR=1): WATER BASED EVAPORATION RATE: (WATER=1): >1 PH (CONCENTRATE): MIN 12.8 DESCRIPTION: CLEAR SOLUTION VOLATILE: 25% SOLUBILITY IN WATER: COMPLETE SPECIFIC GRAVITY: 1.18-1.24 VISCOSITY: 25 CPS @ 68 °F

SECTION IV

FIRE AND EXPLOSION HAZARDS

FLASH POINTS: NON-COMBUSTIBLE

FLAMMABLE LIMITS LEL/UEL: N/A

METHOD USED: CLEVELAND OPEN CUP

EXTINGUISHING MEDIA: WATER SPRAY, FOAM, CARBON DIOXIDE MAY BE USED.

UNUSUAL FIRE OR EXPLOSIVE HAZARD: MAY GENERATE HYDROGEN GAS, AND EVOLVE LARGE AMOUNT OF HEAT UPON CONTACT WITH ZINC, ALUMINUM, TIN, AND OTHER ACTIVE METALS.

SECTION V HEALTH HAZARD DATA

SIGNS AND SYMPTOMS OF EXPOSURE (SKIN, EYE CONTACT; INHALATION; INGESTION)

EYE CONTACT	:	VAPOR, LIQUID, AND MISTS ARE CORROSIVE TO EYES. BRIEF CONTACT OF THIS MATERIAL WILL CAUSE SEVERE DAMAGE TO EYES. SERIOUS INJURY MAY INCLUDE PERMANENT IMPAIRMENT OF VISION, EVEN BLINDNESS IF NOT PROMPTLY AND PROPERLY TREATED.
INHALATION	:	MAY CAUSE SEVERE IRRITATION OF NOSE, MOUTH. EXCESSIVE EXPOSURE MAY CAUSE SEVERE INJURY TO UPPER RESPIRATORY TRACT AND LUNGS.
INGESTION	:	CAN CAUSE IRRITATION OR SEVERE BURN TO MOUTH, THROAT, AND GASTROINTESTINAL TRACT. MAY ALSO CAUSE ULCERATION. SWALLOWING LARGE QUANTITIES MAY RESULT IN DEATH.
SKIN CONTACT	:	SHORT, SINGLE EXPOSURE MAY CAUSE BURN TO SKINS. PROLONGED LIQUID CONTACT WILL BURN AND DESTROY SURROUNDING TISSUES.
First aid measures		
Eye contact	:	IMMEDIATELY AND IMPERATIVELY FLUSH EYES WITH LOTS OF RUNNING WATER FOR AT LEAST 15 MINUTES, LIFTING THE UPPER AND LOWER EYELIDS TO ENSURE FLUSHING OF THE ENTIRE SURFACE. PROMPT MEDICAL ATTENTION IS ESSENTIAL.
INHALATION	:	REMOVE TO FRESH AREA. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. CALL A PHYSICIAN IMMEDIATELY.
INGESTION	:	DO NOT INDUCE VOMITING. DRINK LARGE QUANTITIES OF WATER AND TRANSPORT VICTIM TO MEDICAL FACILITY IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
SKIN CONTACT	:	WASH SKIN WITH LOTS OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND SHOES; WASH BEFORE REUSE. IF IRRITATION OCCURS AND PERSISTS SEEK MEDICAL ATTENTION.

SECTION VI

REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): AVOID MIXING OF THIS MATERIAL WITH STRONG ACIDS OR OXIDIZERS. Also avoid metals such as aluminum, tin, galvanized zinc, brass and bronze. Do not contact with trichloroethylene since dichloro- acetylene may spontaneously be formed.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

CONDITIONS TO AVOID: EXCESSIVE HEAT AND ANY CONTAMINATION.

HAZARDOUS DECOMPOSITION: FLAMMABLE HYDROGEN GAS WILL BE LIBERATED UPON CONTACT WITH SOME METALS SUCH AS ALUMINUM.

SECTION VII

SPILL OR LEAK PROCEDURES

CLEAN-UP PROCEDURES: ONLY TRAINED AND PROPERLY PROTECTED PERSONNEL SHOULD BE INVOLVED IN SPILLED CLEAN-UP OPERATIONS. WEAR ALKALINE-RESISTANT SUIT AND COMPLETE PROTECTIVE EQUIPMENTS INCLUDING RUBBER GLOVES, RUBBER BOOTS, AND SELF-BREATHING APPARATUS DURING CLEAN-UP OPERATIONS. MOP UP AND PLACE MATERIAL IN SEALABLE WASTE CONTAINERS FOR DISPOSAL. KEEP OUT OF SEWERS, STORM DRAINS, SURFACE WATER. FLUSH CONTAMINATED AREAS WITH WATER.

RECOMMENDED WASTE DISPOSAL METHOD: THE MATERIALS RESULTED FROM THE CLEAN-UP OPERATIONS MAY BE HAZARDOUS; THEREFORE, ARE SUBJECTED TO SPECIFIC REGULATIONS. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. ENSURE THAT ALL APPLICABLE AGENCIES RECEIVE PROPER NOTIFICATION OF SPILL AND DISPOSAL METHODS.

SECTION VIII SPECIAL PROTECTION DATA

RGANIC
SHOES.
FOR USE.
•

SECTION IX

SPECIAL PRECAUTION

HYGIENIC PRACTICES IN HANDLING STORING: WASH THOROUGHLY AFTER HANDLING.

PRECAUTION TO BE TAKEN IN HANDLING AND STORING: STORE IN COOL, DRY, VENTILATED AREAS. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. DO NOT USE PRESSURE TO EMPTY CONTAINERS.

DISPOSAL OF EMPTY CONTAINER: EMPTY CONTAINERS SHOULD BE TRIPLE RINSED WITH WATER AND DISPOSED OF PURSUANT TO LOCAL, STATE, AND FEDERAL REQUIREMENTS.

SECTION X

USER'S RESPONSIBILITY

THE RESPONSIBILITY TO PROVIDE A SAFE WORKPLACE REMAINS WITH THE USER. THE USER SHOULD CONSIDER THE HEALTH HAZARD AND SAFETY INFORMATION CONTAINED HEREIN AS A GUIDE AND SHOULD TAKE THOSE PRECAUTIONS REQUIRED IN AN INDIVIDUAL OPERATION TO INSTRUCT EMPLOYEES AND DEVELOP WORK PRACTICE PROCEDURES FOR A SAFE WORK ENVIRONMENT.

THE INFORMATION CONTAINED HEREIN, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, IS ACCURATE. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.