Plus+ Series
Laboratory Refrigerators

The **LabRepCo FUTURA PLUS+ Series Laboratory Refrigerators** are designed for many different applications in the research and clinical market requiring more rigorous temperature control and construction features. These refrigerators are available in a wide range of sizes, come standard with either solid or hinged/sliding glass doors, and feature a microprocessor temperature controller.



LABL-27-HG

Standard Product Features:

- Cycle, auto defrost
- +2°C to +8°C average operating temperature
- Temperature controller with digital display, Hi/Low alarm, and remote alarm contacts
- ENERGY Star Certified
- HFC-free refrigerant (R290a), polyurethane foamed in place insulation
- Heavy duty wire shelves
- Interior fluorescent lights
- Fin and tube, forced air evaporator
- Forced air circulation
- Fin and tube compressor
- Adjustable thermostat
- White powder coat steel interior and exterior
- Self-closing glass door(s) with positive seal
- 4 heavy duty swivel casters (locking)
- Key lock doors
- Access port (1/2")
- 115V operation
- UL listed
- Warranty: 7 years parts and labor



Microprocessor Temperature Controllers

LABRepCo
An Employee-Owned Company

101 Witmer Road, Suite 700 Horsham, PA 19044 | www.labrepco.com | (800) 521-0754 | sales@labrepco.com

Specifications and Ordering Information:



LABL-66-SG



LABL-49-SD

Model #	Cu. Ft. Interior	Number of Shelves	Number of Doors	Door Type	Exterior Dimensions H"	Exterior Dimensions W"	Exterior Dimensions D"	Interior Dimensions H"	Interior Dimensions W"	Interior Dimensions D"	Running Amps/ Breaker	Crated Weight (lbs.)
LABL-23-HG	23	5	1	Glass	81	27	32	55	24	28 1/2	3/15	440
LABL-23-SD	23	5	1	Solid	81	27	34	55	24	28 1/2	3/15	440
LABL-27-HG	27	5	1	Glass	81	30	32	55	27	28 1/2	3/15	440
LABL-27-SD	27	5	1	Solid	81	30	34	55	27	28 1/2	3/15	440
LABL-38-SG	38	10	2	Glass	81	43 1/2	32	55	40 1/2	27	8.8/15	550
LABL-45-SG	45	10	2	Glass	81	52	32	55	49	27	5/15	610
LABL-49-HG	49	10	2	Glass	81	52	32	55	47 1/2	28 1/2	8.8/15	610
LABL-49-SD	49	10	2	Solid	81	52	34	55	47 1/2	28 1/2	5/15	610
LABL-66-SG	66	15	3	Glass	81	75	32	55	72	27	6.2/15	850
LABL-74-HG	72	15	3	Glass	81	75	32	55	72	27	6.2/15	850
LABL-74-SD	72	15	3	Solid	81	75	34	55	72	27	6.2/15	850

Please Note: All dimensions are nominal. All specifications subject to change without notice.

Receptacle Required



115V/1PH/ 60Hz
NEMA-5-15R

LABRepCo
An Employee-Owned Company

101 Witmer Road, Suite 700 Horsham, PA 19044 | www.labrepco.com | (800) 521-0754 | sales@labrepco.com