

## Glass Door Stainless Steel Laboratory Refrigerators

**FUTURA PLUS+ Series glass door stainless steel refrigerators** are designed for many different applications in the research and clinical market requiring more rigorous temperature control and construction features. These refrigerators feature hinged glass self-closing doors, temperature controller with audible and visual alarms, remote alarm contacts, digital temperature display and swivel casters. Available in 23 to 72 cu. ft. sizes. They are available in sizes to fit any storage necessity.



LABL-49-HGSS

### Standard Product Features:

- Cycle, auto defrost
- +2°C to +8°C average operating temperature
- Temperature controller with digital display, Hi/Low alarm and remote alarm contacts
- HFC-free refrigerant (R290a), polyurethane foamed in place insulation
- Heavy duty, epoxy coated wire shelves
- Interior fluorescent light(s)
- Fin and tube, forced air evaporator
- Forced air circulation
- Fin and tube compressor
- Adjustable thermostat
- Stainless steel interior and exterior with glass door(s)
- Heavy duty swivel casters (locking)
- Key lock door(s)
- Access port (1/2")
- 115V operation
- UL listed
- Warranties: 3 years parts and labor, 4 years compressor parts only



**Hydrocarbon refrigerant** used in all LABL Stainless Steel models



**ENERGY Star Certified** on select models



**Microprocessor Temperature Controllers**



LABL-27-HGSS



LABL-23-HGSS



LABL-72-HGSS

| Models              | LABL-23-HGSS     | LABL-27-HGSS    | LABL-49-HGSS    | LABL-72-HGSS    |
|---------------------|------------------|-----------------|-----------------|-----------------|
| Crated Weight lbs.  | 440              | 440             | 610             | 850             |
| Overall Height in.  | 81               | 81              | 81              | 81              |
| Overall Width in.   | 27 1/4           | 30              | 52              | 75              |
| Overall Depth in.   | 33 3/4           | 33 3/4          | 33 3/4          | 33 3/4          |
| Interior Height in. | 55               | 55              | 55              | 55              |
| Interior Width in.  | 24               | 27              | 47 1/2          | 72              |
| Interior Depth in.  | 28 1/2           | 28 1/2          | 28 1/2          | 27              |
| Interior cu. ft.    | 23               | 27              | 49              | 72              |
| Number of Shelves   | 3                | 3               | 6               | 9               |
| Number of Casters   | 4                | 4               | 4               | 4               |
| Refrigerant         | R290a            | R290a           | R290a           | R290a           |
| Voltage Description | 115V, 1PH, 60 Hz | 115, 1PH, 60 Hz | 115, 1PH, 60 Hz | 115, 1PH, 60 Hz |
| Plug Configuration  | 5-15P NEMA       | 5-15P NEMA      | 5-15P NEMA      | 5-15P NEMA      |

Please Note: All dimensions are nominal. All specifications subject to change without notice.

Receptacle Required



115V/1PH/ 60Hz  
NEMA-5-15R

## Solid Door Stainless Steel Laboratory Refrigerators

**FUTURA PLUS+ Series solid door stainless steel refrigerators** are designed for many different applications in the research and clinical market requiring more rigorous temperature control and construction features. These refrigerators feature hinged glass self-closing doors, temperature controller with audible and visual alarms, remote alarm contacts, digital temperature display and swivel casters. Available in 23 to 72 cu. ft. sizes. They are available in sizes to fit any storage necessity.



LABL-27-SDSS

### Standard Product Features:

- Cycle, auto defrost
- +2°C to +8°C average operating temperature
- Temperature controller with digital display, Hi/Low alarm and remote alarm contacts
- HFC-free refrigerant (R290a), polyurethane foamed in place insulation
- Heavy duty, epoxy coated wire shelves
- Interior fluorescent light(s)
- Fin and tube, forced air evaporator
- Forced air circulation
- Fin and tube compressor
- Adjustable thermostat
- Stainless steel interior and exterior with solid stainless steel door(s)
- Heavy duty swivel casters (locking)
- Key lock door(s)
- Access port (1/2")
- 115V operation
- UL listed
- Warranties: 3 years parts and labor, 4 years compressor parts only



**Hydrocarbon refrigerant** used in all LABL Stainless Steel models



**ENERGY Star Certified** on select models



**Microprocessor Temperature Controllers**

Specifications and Ordering Information:




LABL-23-SDSS

LABL-49-SDSS

LABL-72-HGSS

| Models              | LABL-23-SDSS     | LABL-27-SDSS     | LABL-49-SDSS     | LABL-72-SDSS     |
|---------------------|------------------|------------------|------------------|------------------|
| Crated Weight lbs.  | 440              | 440              | 610              | 850              |
| Overall Height in.  | 81               | 81               | 81               | 81               |
| Overall Width in.   | 27 1/4           | 30               | 52               | 75               |
| Overall Depth in.   | 33 3/4           | 33 3/4           | 33 3/4           | 33 3/4           |
| Interior Height in. | 55               | 55               | 55               | 55               |
| Interior Width in.  | 24               | 27               | 47 1/2           | 72               |
| Interior Depth in.  | 28 1/2           | 28 1/2           | 28 1/2           | 27               |
| Interior cu. ft.    | 23               | 27               | 49               | 72               |
| Number of Shelves   | 3                | 3                | 6                | 9                |
| Number of Casters   | 4 (locking)      | 4 (locking)      | 4 (locking)      | 4 (locking)      |
| Refrigerant         | R290a            | R290a            | R290a            | R290a            |
| Voltage Description | 115V, 1PH, 60 Hz | 115V, 1PH, 60 Hz | 115V, 1PH, 60 Hz | 115V, 1PH, 60 Hz |
| Plug Configuration  | 5-15P NEMA       | 5-15P NEMA       | 5-15P NEMA       | 5-15P NEMA       |

Please Note: All dimensions are nominal. All specifications subject to change without notice.

Receptacle Required  
 115V/1PH/ 60Hz  
 NEMA-5-15R

