

Medical Grade Refrigerator/Freezer Combo For Vaccine Storage

CliniCool® Silver Series Medical Grade combo refrigerator/freezer units for vaccine storage are ideal for pharmacies, doctors offices and other medical facilities with limited space. These stacked style combo units offer superior temperature performance and vaccine/sample security that meets federal and state guidelines.



LHP-12-RFC-CA-PH

LHP-7-RFCG-PH

LHP-9-RFCSD-PH

Standard Product Features:

- Manual or Auto defrost freezer with cycle defrost refrigerator
- -13°F (-25°C) freezer operating temperature; +39.2°F (4°C) refrigerator operating temperature
- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- White powder coat exterior (LHP-9-RFCSS-PH stainless steel exterior)
- All combination units are stacked and meet CDC requirements with separate compressors, power cords and temperature controllers
- HFC-free refrigerant (R600a), foam insulation and packaging
- Keyed lock doors
- Magnetic door gaskets for positive seal
- Probe access ports (3/8") - one for refrigerator, one for freezer
- Pharmacy refrigerator/freezer toolkit
- 115V operation (requires two outlets)
- CDC approved power cords
- Remote alarm contacts
- Heavy duty wire shelf
- Leveling legs
- Warranties: 2 years parts and labor, 5 years compressor parts only.



Hydrocarbon refrigerant used in all combo LHP models

Vaccine Compliant Features

All units tested and certified to maintain temperatures within refrigerated or frozen ranges required by the CDC

(2) Thermometers with 3 years NIST Certified of Calibration

Vaccine Storage Power Cord Warning Label

Vaccine Toolkit

Specifications and Ordering Information:

LHP-7-RFCAG-PH



LHP-9-RFCSS-PH

Model		LHP-7-RFCG-PH	LHP-7-RFCAG-PH	LHP-7-RFCG-CA-PH	LHP-9-RFCG-PH	LHP-9-RFCSS-PH	LHP-9-RFCSD-PH
Weight lbs		135	135	135	200	200	200
Overall Height in.		53 1/8	53 1/8	53 1/8	66 3/4	66 3/4	66 3/4
Overall Width in.		23 5/8	23 3/4	23 3/4	23 3/4	23 3/4	23 3/4
Overall Depth in.		24 1/4	24 1/4	24 1/4	25 1/2	24 1/2	24 1/2
Interior Height in.	Refrig.	26 3/4	26 3/4	26 3/4	24 1/2	24 1/2	24 1/2
	Freezer	13 7/8	13 7/8	12 3/8	24 1/2	24	24 1/2
Interior Width in.	Refrig.	19 7/8	19 7/8	19 7/8	19 1/4	19 1/4	19 1/4
	Freezer	17 3/4	18	17 3/4	19	19	19
Interior Depth in.	Refrig.	16	16	16	17 1/4	17 1/2	17 1/4
	Freezer	16	9 1/8	7 1/2	17 1/4	17 1/4	17 1/4
Interior cu. ft.	Refrig.	5.2	5.2	5.2	4.6	4.5	4.6
	Freezer	1.7	1.3	1	4.2	4.2	4.2
# of Shelves:	Refrig.	3 adj	3 adj	3 adj	1 fixed; 2 adj	1 fixed; 2 adj	1 fixed; 2 adj
	Freezer	2 adj	2 adj	2 adj	2 fixed	2 fixed	2 fixed
Defrost Type	Refrig.	Cycle	Cycle	Cycle	Cycle	Cycle	Cycle
	Freezer	Manual	Auto	Controlled Auto	Manual	Manual	Manual
Temperature:	Refrig.	+35°F to +46°F	+36°F to +46°F	+36°F to +46°F	+36°F to +46°F	+36°F to +46°F	+36°F to +46°F
	Freezer	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F
Compressor Size HP	Refrig.	1/6	1/6	1/6	1/8	1/8	1/8
	Freezer	1/8	1/8	1/8	1/8	1/8	1/8
Plug (Receptacle)		5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)
Total Amp Draw	Refrig.	1.3	1.3	1.3	1.74	1.74	1.74
	Freezer	1	1	1	1.5	1.5	5
Voltage		115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz



LHP-12-RFCSD-PH

Model		LHP-12-RFCSD-PH	LHP-12-RFC-CA-PH	LHP-12-RFCASD-PH	LHP-12-RFCAG-PH	LHP-12-RFCG-PH	LHP-12-RFCG-CA-PH
Weight lbs		219	219	219	246	246	246
Overall Height in.		80 1/4	80 1/4	80 1/4	80 1/4	80 1/4	80 1/4
Overall Width in.		23 5/8	23 3/4	23 3/4	23 3/4	23 5/8	23 3/4
Overall Depth in.		26 1/2	26 1/2	26 1/2	26 1/2	26 1/2	26 1/2
Interior Height in.	Refrig.	53 1/2	53 1/2	53 1/2	53 1/2	53 1/2	53 1/2
	Freezer	13 7/8	12 3/8	13 7/8	13 7/8	13 7/8	12 3/8
Interior Width in.	Refrig.	19 7/8	19 7/8	19 7/8	19 7/8	19 7/8	19 7/8
	Freezer	17 3/4	17 3/4	18	18	17 3/4	17 3/4
Interior Depth in.	Refrig.	18 3/8	18 3/8	18 3/8	18 3/8	18 3/8	18 3/8
	Freezer	16	7 1/2	9 1/8	9 1/8	16	7 1/2
Interior cu. ft.	Refrig.	10.5	10.5	10.5	10.5	10.5	10.5
	Freezer	1.7	1	1.3	1.3	1.7	1
# of Shelves:	Refrig.	6 adj	6 adj	6 adj	6 adj	6 adj	6 adj
	Freezer	2 adj	2 adj	2 adj	2 adj	2 adj	2 adj
Defrost Type	Refrig.	Cycle	Cycle	Cycle	Cycle	Cycle	Cycle
	Freezer	Manual	Controlled Auto	Manual	Auto	Manual	Controlled Auto
Temperature:	Refrig.	+36°F to +46°F	+36°F to +46°F	+36°F to +46°F	+36°F to +46°F	+36°F to +46°F	+35.6°F to +46.4°F
	Freezer	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F
Compressor Size HP	Refrig.	1/3	1/3	1/3	1/3	1/3	1/3
	Freezer	1/8	1/8	1/8	1/8	1/8	1/8
Plug (Receptacle)		5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)	5-15P (5-15R)
Total Amp Draw	Refrig.	2.3	2.3	2.3	2.3	2.3	2.3
	Freezer	1	1	1	1	1	1
Voltage		115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz

Please Note: All dimensions are nominal. All Specifications subject to change without notice.

Receptacle Required



115V/1PH/ 60Hz
NEMA-5-15R

