



The Pulse 150™ Ultrasonic Homogenizer uses cavitation and ultrasonic waves to break cells in suspension, shear DNA and prepare samples for ChIP assays. With up to 150 watts of power, the unit can process samples from 0.1 ml to 150 ml (with the appropriate horn).

All components needed for homogenization are included with the Pulse 150 - a controller, transducer, temperature probe, 6 mm diameter titanium alloy horn and wrenches to change horns. A soundproof box with sample platform is also supplied as standard. The box helps to reduce the noise generated by the sonicator. The 6mm horn is appropriate for volumes from 10ml to 100ml. Optional horns are available for other volumes.

Operating parameters are set and viewed on the 4.3" color touch screen. Pulsed operation is easily programmed as is the power level. Twenty programs can be stored in memory and recalled as needed. Alarms alert the user to over temperature, over/no load and expiration of time.

Horn	- u			-
Horn size	2mm	3mm	6mm*	8mm
Process capacity	0.1 - 5ml	3-10ml	10-100ml	20-150ml
Power ratio	1 - 45%	1 - 55%	1 - 75%	1 - 90%

<sup>\*</sup>Supplied with Pulse 150



Pulse 150 Home Screen



Supplied with soundproof box and integrated stand

## **Technical Data**

Power 1.5 - 150 W, continuously adjustable

Frequency 20 - 25 KHz Cycle time (pulse on/off) 0.1 - 99.9 sec

Timer 1 sec - 99 hours, 59 min, 59 sec

Duty cycle 0.1 - 99.9% Volume\* 0.1 - 150 ml Program memory 20 programs

Display/control 4.3" full color touch screen
Horn 6mm titanium (others available)
Alarms No load, over load, end of run,

over temperature

Controller

Dimensions (W x D x H) 12 x 18.5 x 16.9 in.

30.5 x 47 x 43 cm

Weight 35.3 lbs/16 kg

Soundproof enclosure

Dimensions (W x D x H) 13.8 x 13.8 x 21.7 in.

35 x 35 x 55 cm

Weight 22 lb/10 kg

Electrical 120 or 240V, 50/60Hz

Warranty 2 years

\*Volume dependent upon the installed horn. Supplied with 6mm horn for volumes 10 - 100 ml.

## **Ordering Information**

DP0150\* Pulse 150 Ultrasonic Homogenizer, complete with controller, transducer, 6mm horn and soundproof enclosure

DP0150-2 Horn, 2 mm diameter, for 0.1 - 5 ml
DP0150-3 Horn, 3 mm diameter, for 3 - 10 ml

DP0150-3 Horn, 3 mm diameter, for 3 - 10 ml
DP0150-6 Horn, 6 mm diameter, for 10 - 100 ml
DP0150-8 Horn, 8 mm diameter, for 25 - 150 ml
\*115V with US plug. For EU plug, please add -E to cat no.

For information on the entire line of Benchmark homogenizers, including handheld rotor stator units and bead homogenizers, visit our website: www.benchmarkscientific.com



PO Box 709, Edison NJ 08818 TEL: 908 769-5555 FAX: 732 313-7007
Web: www.BenchmarkScientific.com Email: info@BenchmarkScientific.com