

PROTECTING YOUR DNA SAMPLES FROM CONTAMINATION

UV PCR CABINET



UV PCR Workstation

DESCRIPTION & OPERATION

When undertaking PCR reactions it is important to protect against contamination by rogue DNA. The cabinet, reagents and equipment must be thoroughly decontaminated prior to a PCR procedure. UV irradiation is an efficient decontaminator, breaking down DNA sequences so that replication cannot occur in a subsequent amplification process.

The necessary UV exposure times vary from as little as 5 minutes to a maximum of 30 minutes.

The UV PCR workstation protects against contamination by bathing the PCR apparatus in sterile air and limiting risk of contamination from the operator's arms, or from any equipment bought into the otherwise sterile environment. A positive pressure ensures that there is no ingress of airborne contaminants from the surrounding laboratory environment.

Acrylic windows offer exceptionally clear all round vision and additionally do not allow transmission of UV.

FEATURES OF UV PCR CABINET

- Powerful UV tube lights are combined with carefully located optical reflectors to ensure uniform intensity distribution of the UV radiation throughout the cabinet
- Control system allows the choice of timed UV exposure from 5-30 minutes
- Door sensors switch off UV lamps if door flap is opened, ensuring operator safety
- Acrylic protects the operator from beta emissions from commonly used 32P labelled compounds
- Cabinet is supplied with handy corner shelves, which do not hinder the working area. Door flaps offer excellent access to the cabinet interior
- 18W white lights, operated from an external switch, illuminate cabinet interior
- Side panels include ports for cable access
- Filtration system delivers air to ISO5 quality
- Automatic fan speed increase on door opening maintains air velocity to 0.45m/s (88 fpm) at the workstation front
- Electronic filter saturation indicator
- Fan noise level <50 dBA



BC UV Sterilisation Hood

FILTRATION & STANDARDS

Pre-filtration eliminates particles at 5.0µm or larger to an efficiency of 92% as defined in BS EN ISO 779.

HEPA filtration (H14 Standard) eliminates particles 0.3 microns or greater to an efficiency of 99.997% providing ultra-clean particle free Class 5 BS EN ISO 14644-1:1999 air conditions.

► MORE ABOUT CARON

Caron has been designing, manufacturing and maintaining just about every conceivable style of clean air cabinet for more than 35 years. Caron has grown from a national business to become a company with links worldwide and now enjoys an unrivalled reputation as the world's most innovative supplier in this specialist sector.

In addition to UV PCR Cabinets, Caron manufactures ductless fume cabinets, biological safety cabinets, chemical storage cabinets, laminar flow cabinets, powder weighing cabinets and laboratory automation & robotics system enclosures.

TECHNICAL SPECIFICATIONS

Model	Description	External dims (WxDxH)	Internal dims (WxDxH)
800mm	PCR Cabinet, supplied with UV and lighting	802 x 549 x 998 mm (31.5" x 21.6" x 39.3")	730 x 489 x 699 mm (28.7" x 19.2" x 27.5")

Cabinets available for power supply: 230V, AC, 50/60Hz, 5Amp, 1Ø and 115V, AC, 60Hz, 8Amp, 1Ø. PCR is covered by U.S patents owned by Hoffmann-La Roche Inc.

► STATIC OR MOBILE BENCH

To make your cabinet truly portable, either select a mobile bench with integrated cupboard or an open box selection bench. Alternatively a static stand with levelling/adjustable feet may be selected (an adjustable height electronic model is available).



TECHNICAL SPECIFICATIONS

Description

Mobile Bench robust epoxy coated pressed steel construction, cupboard doors with magnetic catches and lockable 130mm castors.

► QUALITY ASSURED

CE Caron 230V systems are CE marked

Caron manufactures from UL listed components

CARON PRODUCTS & SERVICES, INC.
PO Box 715 / Marietta OH 45750 / PHONE 740 373 6809 / 800 648 3042 / FAX 740 374 3760

United Kingdom Office:
4/5 Piper's Wood Industrial Park / Waterberry Drive / Waterlooville / Hampshire. P07 7XU. UK.
PHONE: +44 (0)23 9226 6400 / FAX: +44 (0)23 9226 3373

