

FreeZone 12 Liter -50C Console Freeze Dryer with Stoppering Tray Dryer



View online: <https://www.labconco.com/product/freezone-12-liter-50c-console-freeze-dryer-with-stoppering-tray-dryer/6351>



Overview

FreeZone 12 Liter Console Freeze Dryers with Stoppering Tray Dryers are designed for lyophilizing moderate to large loads and stoppering vials or serum bottles under vacuum. The console features a front viewing window and interior space for a vacuum pump (sold separately).

The console's upright stainless steel collector coil is capable of holding 12 liters before defrosting. A single 1 hp HCFC/CFC-free refrigeration system cools the collector to -50° C (-58° F), suitable for aqueous samples.

The Stoppering Tray Dryer features three 16.5" x 12" processing shelves. A single 1 hp HCFC/CFC-free refrigeration system and 1000-watt electric heater cool and heat the fluid medium circulating through channels in the shelves.

[Lyo-Works™ OS](#) provides a real time display of freeze dryer and tray dryer parameters on a 5" full color, capacitive touch screen. Models with PTFE-coated collectors that can withstand corrosive compounds are available.

Catalog Number: 701221010

- [Stay Connected](#)
- [View Real-Time Sample Data](#)
- [Get Consistent, High Quality Results](#)
- [Make Challenging Samples Easy](#)

Vacuum pump and freeze dry glassware (if not bulk freeze drying) are required (not included).

Specifications

- **Weight:** 698.0 lbs
- **Weight metric:** 316.6 kg
- **Dimensions:** 32.4" w x 29.6" d x 63.7" h
- **Dimensions metric:** 82.2 w x 75.1 d x 161.7 h cm
- **Electrical:** 230V, 60 Hz, 9A (console); 230V, 60 Hz, 9A (tray dryer)
- **Region:** International, U.S. and Canada
- **Collector Temperature:** -50° C, -58° F
- **Conformance:** CAN/CSA C22.2, UL
- **Ice Holding Capacity:** 12L
- **Options Included:** Stoppering Tray Dryer
- **Plug Type:** North America, 230V
- **Style:** Console
- **Vacuum Pump Displacement Required:** 163 L/min or larger displacement

Description

Features (All Models)

- Upright stainless steel collector coil capable of holding 12L of ice before defrosting. Acrylic collector lid, 3/4" thick, has neoprene gasket.
- Console cabinet with interior space for vacuum pump (sold separately) and two-piece, removable front panel with viewing window.
- Clear acrylic chamber lid, 3/4" thick, with neoprene gasket.
- [FreeZone Stoppering Tray Dryer](#).
- Brushed stainless steel and glacier white, powder-coated steel exterior with blue accents.
- Full color, 5" capacitive touch screen with Lyo-Works™ OS:
 - Real time display of collector temperature, vacuum level, and optional End-Zone™ end point detection system.
 - Start-up mode for collector cool-down and vacuum pull-down (automatic or manual).
 - Operating mode (standby or run).
 - Vacuum set point, alerts, diagnostic tests, user manual, defrost control, and optional drying accessory parameters.
 - Data logging stores and displays data in table or chart format, and may be exported via USB or Ethernet.
 - Settings include language (English, Spanish, French, German, or Italian), time, time zone, temperature (° C or ° F), and vacuum (mBar, Torr, or Pa).
 - Alerts are programmable to send via Ethernet connection to user-entered email addresses.
 - Display settings include brightness, touch sounds (on/off), and screen time out in minutes (on/off).
 - Maintenance alert settings include vacuum pump oil change, refrigeration cleaning, total operating hours and line voltage offset.
 - Level-specific security lock-out prevents changes to programs and other system parameters.
- Hot gas defrost with auto shut off at +60° C (+140° F).
- On/standby switch.
- Moisture sensor that prevents refrigeration or vacuum start-up when moisture is detected in the drain line.
- Vacuum control valve that maintains vacuum level set point.
- Vacuum break valve that bleeds air into the system when power to the freeze dryer or vacuum pump is shut off. If a power outage less than approximately 5 minutes occurs, the freeze dryer will restart and the refrigeration and vacuum system will resume operation once power is restored. If the power failure is more than approximately 5 minutes and the collector warms above safe limits, the freeze dryer will not automatically restart.
- Side-mounted USB port and rear-mounted Ethernet connection.
- Front-mounted, quick-disconnect drain hose fitting and side-mounted lanyard with hose connector. 18", 1/4" ID silicone tubing and clamp included.
- Internal electrical receptacle for vacuum pump connection.
- 3-wire electrical cord with plug.
- 3/4" OD vacuum connection, 36" of 3/4" ID vacuum hose and two clamps.


Options Include

- PTFE-coated collector coil and chamber for processing involving corrosive compounds.
- Purge valve for isolating the vacuum pump from the freeze dryer.
- Region-specific electrical plug configurations.

Required Accessories (Not Included)

- Vacuum pump with a displacement of at least 163 L/min, 0.002 mBar ultimate pressure and fitting suitable for 3/4" ID vacuum hose.
- Freeze dry glassware if not bulk freeze drying.

For Product Assistance



[Joe Amoriello](#)
Sales Representative



[Kara Johnson](#)
Customer Coordinator



Labconco Corporation
8811 Prospect Avenue
Kansas City, MO 64132-2696
Phone: (816) 333-8811

